HUBTRACTYRES
JOURNEY TO THE FUTURE

Premium Selections of Truck Tires

Experience peak performance with our premium truck tire collection. Crafted for durability and precision, our high-end tires redefine excellence on the road.

info@hubtractyre.com
Ali@hubtractyre.com
HTTPS://WWW.HUBTRACTYRE.COM
0086-136 0391 5955

HIGHWAY T21

Selling point

- Decoupling groove helps resist uneven shoulder wear.
- Stone ejectors in the bottom of the tread groove protect the casing from stones penetrations and help resist stone retention.
- The linear 4-groove pattern offers straight drivability in all conditions.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142M	6175	105	5840	105	41.10	10.98	12.0
2	11R22.5	8.25	16	146/143M	6610	120	6005	120	41.10	10.98	12.0
3	295/75R22.5	9.00	14	144/141M	6175	110	5675	110	39.92	11.73	12.0
4	295/75R22.5	9.00	16	146/143M	6610	120	6005	120	39.92	11.73	12.0

HIGHWAY T12

Selling point

- Suitable for on-highway trailer application.
- Reduces weight for increased playload(VS duals)
- Construction optimized for fuel economy and long life.
- Special tread design for fuel economy.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	445/50R22.5	14.00	20	161L	10200	120	-	-	40.07	17.52	13.2

Remark : The above technical data are for reference only .

HIGHWAY D22

Selling point

- Closed shoulder delivers smooth wear, fuel efficiency and reinforced stability.
- Main 6 zigzag groove provides good traction performance.
- 3D Xerf reinforces inter-locking between blocks and it delivers great traction performance, stability and even wear.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	445/50R22.5	14.00	18	158L	9370	110	—	—	40.07	17.52	24.0
2	445/50R22.5	14.00	20	161L	10200	120	—	—	40.07	17.52	24.0

HIGHWAY D16

Selling point

- Shoulder and center block design provides traction in all conditions.
- Low heat generation with semi-open shoulder grooves.
- Variable zigzag groove help to reduce groove crack.
- Strong carcass materials help promote tire durability and provide tire retreadability.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142M	6175	105	5840	105	41.92	10.98	27.7
2	11R22.5	8.25	16	146/143M	6610	120	6005	120	41.92	10.98	27.7
3	11R24.5	8.25	14	146/143M	6610	105	6005	105	43.93	10.98	27.7
4	11R24.5	8.25	16	149/146M	7160	120	6610	120	43.93	10.98	27.7
5	285/75R24.5	8.25	14	144/141M	6175	110	5675	110	41.81	11.14	27.7
6	285/75R24.5	8.25	16	147/144M	6780	120	6175	120	41.81	11.14	27.7
7	295/75R22.5	9.00	14	144/141M	6175	110	5675	110	40.39	11.73	27.7
8	295/75R22.5	9.00	16	146/143M	6610	120	6005	120	40.39	11.73	27.7

Remark : The above technical data are for reference only .

HIGHWAY S21

Selling point

- Decoupling groove helps resist uneven shoulder wear.
- Straight five-rib tread design with four grooves provides improved handling.
- Micro sipes protect the interior ribs from punch wear;
- Fantastic sidewall design.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142M	6175	105	5840	105	41.30	10.98	19.0
2	11R22.5	8.25	16	146/143M	6610	120	6005	120	41.30	10.98	19.0
3	295/75R22.5	9.00	14	144/141M	6175	110	5675	110	39.92	11.73	19.0
4	295/75R22.5	9.00	16	146/143M	6610	120	6005	120	39.92	11.73	19.0

HIGHWAY D21

Selling point

- Closed shoulder design helps promote uniform wear throughout the life of the tire.
- Optimize proportion of groove and blocks: good traction performance.
- 3D sipes lock together: great traction performance, stability and even wear.
- Reinforcing rib: reinforce traction and stability.

road condition: **Long Haul** | Regional | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142L	6175	105	5840	105	41.92	10.98	28.0
2	11R22.5	8.25	16	146/143L	6610	120	6005	120	41.92	10.98	28.0
3	11R24.5	8.25	14	146/143L	6610	105	6005	105	43.91	10.98	28.0
4	11R24.5	8.25	16	149/146L	7160	120	6610	120	43.91	10.98	28.0
5	285/75R24.5	8.25	14	144/141L	6175	110	5675	110	41.87	11.14	28.0
6	285/75R24.5	8.25	16	147/144L	6780	120	6175	120	41.87	11.14	28.0
7	295/75R22.5	9.00	14	144/141L	6175	110	5675	110	40.39	11.73	28.0
8	295/75R22.5	9.00	16	146/143L	6610	120	6005	120	40.39	11.73	28.0

Remark : The above technical data are for reference only .

HUBTRACTYRES
JOURNEY TO THE FUTURE

WWW.HUBTRACTYRE.COM

REGIONAL S21

Selling point

- Wide shoulder ribs reduce shoulder step wear.
- Combination of center zig grooves and a specially tread depth provides multi performance for better tread life.
- Optimizes the footprint for long and even wear.
- Fantastic sidewall design.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142M	6175	105	5840	105	41.46	10.98	20.0
2	11R22.5	8.25	16	146/143M	6610	120	6005	120	41.46	10.98	20.0
3	295/75R22.5	9.00	14	144/141M	6175	110	5675	110	39.92	11.73	20.0
4	295/75R22.5	9.00	16	146/143M	6610	120	6005	120	39.92	11.73	20.0

REGIONAL S22

Selling point

- Tough tread compound and solid shoulder ribs to resist maneuvering scrub.
- 4 wavy groove provide outstanding traction and drainage performance.
- Protector ribs on both sidewalls to fight damage from curbing, cuts and abrasions.
- Special pattern steel plate design ensures uniform tire wear.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	245/70R19.5	7.50	14	133/131L	4540	110	4300	110	33.03	9.76	17.0
2	245/70R19.5	7.50	16	135/133L	4805	120	4540	120	33.03	9.76	17.0

Remark : The above technical data are for reference only .

REGIONAL D21

Selling point

- Open shoulder design with good tire heat dissipation.
- Main 4 zigzag groove provides good traction performance.
- 3D Kerf reinforces inter-locking between blocks and it delivers great traction performance, stability and even wear.
- The rib of the tread block adopts the hidden groove design to improve the rigidity of the tire crown and ensure the driving performance of the tire.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	245/70R19.5	7.50	14	133/131L	4540	110	4300	110	33.03	9.76	17.0
2	245/70R19.5	7.50	16	135/133L	4805	120	4540	120	33.03	9.76	17.0

REGIONAL D15

Selling point

- Suitable for on-highway long haul and regional drive applications.
- Tread design helps deliver all-season traction and reduction of uneven wear.
- Construction optimized for fuel economy and long life.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	14	144/142L	6175	105	5840	105	41.69	10.98	25.8
2	11R22.5	8.25	16	146/143L	6610	120	6005	120	41.69	10.98	25.8
3	11R24.5	8.25	14	146/143L	6610	105	6005	105	43.70	10.98	25.8
4	11R24.5	8.25	16	149/146L	7160	120	6610	120	43.70	10.98	25.8
5	285/75R24.5	9.25	14	144/141M	6175	110	5675	110	41.57	11.14	25.8
6	285/75R24.5	9.25	16	147/144M	6760	120	6175	120	41.57	11.14	25.8
7	295/75R22.5	9.00	14	144/141M	6175	110	5675	110	40.16	11.73	25.8
8	295/75R22.5	9.00	16	146/143M	6610	120	6005	120	40.16	11.73	25.8

Remark : The above technical data are for reference only .

REGIONAL G11

Selling point

- Significant groove angles to help release stones and reduces damages from stone drilling.
- Construction optimized for long service life.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	215/75R17.5	6.00	14	126/124M	3750	102	3525	102	30.20	8.35	15.7
2	215/75R17.5	6.00	16	135/133J*	4805	123	4540	123	30.20	8.35	15.7

*Recommended for low platform trailer application

REGIONAL G12

Selling point

- Typical zigzag groove design for ture multi-road use.
- Outstanding resistance to high scrub application from larfe solid shoulder.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	425/65R22.5	12.25	20	165J	11400	120			44.25	16.61	22.0

Remark : The above technical data are for reference only .

REGIONAL G15

Selling point

- Massive shoulders and application specific compound help resist scrub and abrasion ,extending tread life.
- Zogzag groove for true all-position use.

road condition: Long Haul | **Regional** | On/Off Road | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	385/65R22.5	11.75	18	158K	9370	120	-	-	42.20	15.31	20.8
2	385/65R22.5	11.75	20	160J	9920	130	-	-	42.20	15.31	20.8

MIXED T11

Selling point

- Typical combined pattern.
- Cut resistance compound.
- Good braking and grip.

road condition: Long Haul | Regional | **On/Off Road** | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	445/65R22.5	13.00	20	168K	12300	120			45.28	17.48	22.7

Remark : The above technical data are for reference only .

MIXED G11

Selling point

- Typical combined pattern.
- Cut resistance compound.
- Good braking and grip.

road condition: Long Haul | Regional | **On/Off Road** | LOGGING

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	16	146/143K	6610	120	6005	120	41.50	10.98	18.9
2	11R24.5	8.25	16	149/146K	7160	120	6610	120	43.46	10.98	20.8
3	255/70R22.5	7.50	16	140/137M	5510	120	5070	120	36.61	10.04	16.0
4	315/80R22.5	9.00	20	157/154K	9090	130	8270	130	42.36	12.28	22.0

MINE D11

Selling point

- Deep and rigid block design for good traction.
- Stone rejectors protect the casing in base of the tread groove.
- New tread compound for resistance to cuts, chips and tearing.
- Recommended for Short Haul Logging drive applications.

road condition: Long Haul | Regional | On/Off Road | **LOGGING**

Product data

No.	Size	Rim	Ply Rating	LI/SS	MaxLoad	MaxPressure	MaxLoad	MaxPressure	Overall Diameter	Section Width	Tread Depth
					(Single-LBS)	(Single-PSI)	(Dual-LBS)	(Dual-PSI)	(in.)	(in.)	(32nds)
1	11R22.5	8.25	16	146/143K	6610	120	6005	120	41.93	10.98	29.0
2	11R24.5	8.25	16	149/146G	7160	120	6610	120	43.94	10.98	31.4

Remark : The above technical data are for reference only .